



Regolatori della pressione di condensazione - omologati da underwriters laboratories inc.
 Condensing pressure regulators - approved by underwriters laboratories inc.
 Régulateurs de pression de condensation - homologués par underwriters laboratories inc.
 Verflüssigungsdruckregler - zugelassen von underwriters laboratories inc.

Disegno Drawing Dessin Zeichnung	N° catalogo Part number N° catalogue Katalog Nr.	Attacchi Connections Raccords Anschlüsse			Campo di regolazione Regulation range Plage de régulation Regelbereich [bar]	Kv [m³/h]	PS [bar]	TS [°C]		Confezione n° pz Package pcs Emballage Verpackung
		SAE Flare	ODS [in.]	ODS [mm]				min	max	
	3340/4	1/2"	-	-	3-20	2,7	28 (1)	- 40	+ 110	15
	3340/5	5/8"	-	-						
	3340/M12S	-	-	12	3-20	2,7	28 (1)	- 40	+ 110	15
	3340/4S	-	1/2"	-						8
	3340/5S	-	5/8"	16						1
	3340/7S	-	7/8"	22						
	3340/9S	-	1.1/8"	-						
	3340/M28S	-	-	28						
	3340/11S	-	1.3/8"	35						
	3345/M12S (2)	-	-	12	12-36	2,7	45	- 40	+ 110	15
	3345/4S (2)	-	1/2"	-						8
	3345/5S (2)	-	5/8"	16						
3345/7S (2)	-	7/8"	22							

Note:

(1)
MWP = 405 psi in conformità a omologazione UL

(2)
non omologato UL

(1)
MWP = 405 psi according to UL approval

(2)
not UL approved


(1)
MWP = 405 psi conformément à homologation UL

(2)
Pas approuvé UL

(1)
MWP = 405 psi in Übereinstimmung zur UL-Zulassung

(2)
Ohne UL-Zertifizierung

Valvole differenziale
Differential valves
Vannes à pression différentielle
Differenzdruckventile

Disegno Drawing Dessin Zeichnung	N° catalogo Part number N° catalogue Katalog Nr.	Attacchi Connections Raccords Anschlüsse			Pressione differenziale d'apertura Opening differential pressure Pression différentielle d'ouverture Öffnungsdifferenzdruck [bar]	Kv [m³/h]	PS [bar]	TS [°C]		Confezione n° pz Package pcs Emballage Verpackung
		SAE Flare	ODS [in.]	OD [mm]				min	max	
	3136W/M12	-	-	12	1,4 - 3	1,5	45	- 40	+ 110	16
	3136W/4	-	1/2"	-						

CLASSIC