

Ikkunakoje ASW-12BI SINCLAIR

Capacity	Cooling	3700	W
Power Supply	-	220 - 240 / 1 / 50	V / Ph / Hz
Application area	-	16 - 24	m ²
Power Input	Cooling	1,030	kW
Rated Power Input	Cooling / Heating	1,3	kW
Power Current	Cooling	4,6	A
Rated power current	-	6,5	A
SEER	-	5,4	-
Energy class	-	A	-
Air flow	Interior	480 / 430 / 380	m ³ / h
Air flow	Exterier	1200	m ³ / h
Sound Pressure Level at 1 m	Interior	50 / 48 / 46	dB(A)
Sound Pressure Level at 1 m	Exterier	58 / 56 / 54	dB(A)
Sound power level	Interior	59 / 57 / 55	dB(A)
Sound power level	Exterier	65 / 63 / 61	dB(A)
Dehumidifying Volume	-	1,6	l / h
Refrigerant / Charge / Eq. CO ₂	-	R32 / 0,63 / 0,43	type / kg / t
Dimension	(w x h x d)	660 x 428 x 700	mm
Package dimension	(w x h x d)	739 x 505 x 793	mm
Net / gross weight	Net / gross weight	50,0 / 54,0	kg
Operating Temperature Range	Cooling	18 ~ 43	°C
Package volume	-	0,296	m ³

Notes

The specification of products is subject to change based further development of the units by the producer and can be changed without prior notice. Refer to rating label.

- Refrigerant: R32 (100% HFC-32) with GWP (Global Warming Potential) 675

The devices contains fluorinated greenhouse gases covered by the Kyoto Protocol. Noise is tested in the semi-anechoic room, so it should be slightly higher in the actual Operation due to environmental change. Power input is tested under standard condition.