

Ikkunakoje ASW-09BI SINCLAIR

Capacity	Cooling	2700	W
Power Supply	-	220 - 240 / 1 / 50	V / Ph / Hz
Application area	-	12 - 18	m ²
Power Input	Cooling	0,782	kW
Rated Power Input	Cooling / Heating	1,1	kW
Power Current	Cooling	3,5	A
Rated power current	-	5,5	A
SEER	-	5,2	-
Energy class	-	A	-
Air flow	Interior	400 /360 / 320	m ³ / h
Air flow	Exterier	800	m ³ / h
Sound Pressure Level at 1 m	Interior	50 / 48 / 46	dB(A)
Sound Pressure Level at 1 m	Exterier	56 / 54 / 52	dB(A)
Sound power level	Interior	59 / 57 / 55	dB(A)
Sound power level	Exterier	65 / 63 / 61	dB(A)
Dehumidifying Volume	-	1,0	l / h
Refrigerant / Charge / Eq. CO ₂	-	R32 / 0,51 / 0,34	type / kg / t
Dimension	(w x h x d)	560 x 375 x 710	mm
Package dimension	(w x h x d)	623 x 425 x 806	mm
Net / gross weight	Net / gross weight	43,0 / 47,0	kg
Operating Temperature Range	Cooling	18 ~ 43	°C
Package volume	-	0,213	m ³

Notes

The specification of products is subject to change based further development of the units by the producer and can be changed without prior notice. Refer to rating label.

- Refrigerant: R32 (100% HFC-32) with GWP (Global Warming Potential) 675

The devices contains fluorinated greenhouse gases covered by the Kyoto Protocol. Noise is tested in the semi-anechoic room, so it should be slightly higher in the actual Operation due to environmental change. Power input is tested under standard condition.