

Kattokasetti SF-300C2 vedellä Sinclair

Power System	Type	220 - 240 / 1 / 50	V / Ph / Hz
Air flow	(H/M/L)	560 / 392 / 280	m3/h
Air flow	(H/M/L)	330 / 231 / 165	CFM
Cooling	Capacity (H/M/L)	3,02 / 2,30 / 1,75	kW
Cooling	Water flow rate	519	l/h
Cooling	Water pressure drop	7,4	kPa
Heating	Capacity (H/M/L)	4,1/3,0/2,2	kW
Heating	Water pressure drop	8,0	kPa
Power System	Input	22,7	W
Sound Pressure Level at 1 m	(H/M/L)	34 / 29 / 21	db(A)
Fan motor	Type	DC motor	-
Fan motor	Quantity	1	-
Fan	Type	Centrifugal, forward-curved blades	-
Fan	Quantity	1	-
Coil	Row	2	-
Coil	Max. working pressure	1,6	MPa
Coil	Diameter	7,0	mm
Outline Dimensions	Panel	647 x 50 x 647	mm
Package Dimensions	Panel	715 x 123 x 715	mm
Net Weight	Panel	2,5	kg
Gross Weight	Panel	4,5	kg
Outline Dimensions	Body	575 x 261 x 575	mm
Package Dimensions	Body	675 x 320 x 675	mm
Net Weight	Body	16,5	kg
Gross Weight	Body	22,5	kg
Connection Pipe Size	Water Inlet / Outlet	G3/4	inch
Connection Pipe Size	Condensate Drain	25	mm
Package volume	Body	0,146	m3
Package volume	Panel	0,063	m3