

Sisäyksikkö MS-H12AISW Sinclair

Capacity	Cooling / Heating	3,5 / 3,8	kW
Air Flow	Indoor Unit	560 - 280	m ³ / h
Sound Pressure Level at 1 m	Indoor Unit	39 / 36 / 34 / 31 / 28 / 27 / 26	dB(A)
Dehumidifying Volume	-	1,4	l / h
Refrigerant Liquid Pipe	Diameter	1/4 / 6,4	inch / mm
Refrigerant Gas Pipe	Diameter	3/8 / 9,5	inch / mm
Dimension (w x h x d)	Indoor Unit	896 x 320 x 159	mm
Package (w x h x d)	Indoor Unit	973 x 403 x 255	mm
Net / Gross Weight	Indoor Unit	11,5 / 14,5	kg
Power Supply	Into Indoor Unit	220–240 / 1 / 50	V / Ph / Hz
Controller	Type	remote	-
Package volume	Indoor unit	0,100	m ³

Notes

The specification of products is subject to change based further development of the units by the producer and can be changed without prior notice. Refer to rating label. Data are based on following conditions:

- Length of connection pipe: 5m
- Cooling condition: indoor temperature 27°C DB / 19°C WB, outdoor temperature 35°C DB / 24°C WB
- Heating condition: indoor temperature 20°C DB / 15°C WB, outdoor temperature 7°C DB / 6°C WB
- Refrigerant: R410A (50% HFC-32, 50% HFC-125) with GWP (Global Warming Potential) 2088

The devices contains fluorinated greenhouse gases covered by the Kyoto Protocol. Noise is tested in the semi-anechoic room, so it should be slightly higher in the actual Operation due to environmental change. Power input is tested under standard condition.