

Sisäyksikkö SINCLAIR ASC-18AIN

Capacity	Cooling / Heating	5 (1,6 - 5,8) / 5,6 (1,4 - 6,8)	kW
Power Supply	Into Indoor Unit	220-240 / 1 / 50	V / Ph / Hz
SEER / SCOP	-	5,6 / 3,8	W / W
Energy Class	Cooling / Heating	A+ / A	-
Air Flow	Indoor Unit	760	m ³ / h
Sound Pressure Level at 1,4 m	-	47 / 46 / 44	dB(A)
Dehumidifying Volume	-	1,8	l / h
Refrigerant / Charge / Eq. CO2	-	R410A / 1,40 / 2,92	type / kg / t
Refrigerant Liquid Pipe	Diameter	1/4 / 6,4	inch / mm
Refrigerant Gas Pipe	Diameter	1/2 / 12,7	inch / mm
Min. / Max. Pipe Length	-	3 / 20	m
Max. Elevation	-	15	m
Max pipe length without additional refrigerant	-	7	m
Additional Refrigerant	-	30	g / m
Dimension (w x h x d)	Indoor Unit	595 x 595 x 240	mm
Dimension (w x h x d)	Panel	650 x 50 x 650	mm
Package (w x h x d)	Indoor Unit	773 x 300 x 733	mm
Package (w x h x d)	Panel	763 x 105 x 763	mm
Net / Gross Weight	Indoor Unit	20,0 / 24,0	kg
Net / Gross Weight	Panel	3,5 / 5	kg
Operating Temperature Range	Cooling	-15 ~ 48	°C
Operating Temperature Range	Heating	- 15 ~ 24	°C
Package volume	Indoor unit	0,170	m ³
Package volume	Panel	0,061	m ³

Notes

The specification of products is subject to change based further development of the units by the producer and can be changed without prior notice. Refer to rating label. Data are based on following conditions:

- Length of connection pipe: 5m
- Cooling condition: indoor temperature 27°C DB / 19°C WB, outdoor temperature 35°C DB / 24°C WB