

Sisäyksikkö SINCLAIR SDV5-100CA

Capacity	Cooling	10,0	kW
Capacity	Heating	11,0	kW
Power Supply	-	220–240 / 1 / 50	V / Ph / Hz
Power Input	-	75	W
Sound Pressure Level at 1,4 m	-	47 / 45 / 43 / 41 / 39 / 37 / 36	dB(A)
Sound power level	-	61 / 59 / 57 / 55 / 53 / 51 / 50	dB(A)
Net Dimension	Body (w x h x d)	840 x 300 x 840	mm
Net Dimension	Panel (w x h x d)	950 x 54,5 x 950	mm
Packing Dimensions	Body (w x h x d)	955 x 330 x 955	mm
Packing Dimensions	Panel (w x h x d)	1035 x 90 x 1035	mm
Net Weight	Body	28,4	kg
Net Weight	Panel	5,0	kg
Gross Weight	Body	33,8	kg
Gross Weight	Panel	8,0	kg
Throttle	Type	Electromagnetic Expansion Valve	-
Design Pressure	-	4,4 / 2,6	MPa
Refrigerant	Type	R410A	-
Pipe Diameter	Liquid Side	9,5	mm
Pipe Diameter	Gas Side	15,9	mm
Pipe Diameter	Drainage Pipe	32	mm
Set Temperature range	-	17 ~ 30	°C

Notes

The specification of products is subject to change based on further development of units by the producer and can be changed without prior notice. Refer to rating label.

R410A (50% HFC-32, 50% HFC-125), GWP of refrigerant used: 2088.

Contains fluorinated greenhouse gases covered by the Kyoto Protocol.