

# Sisäyksikkö Sinclair ASC-36BI

<b>Power Supply</b>	Into Indoor Unit	220–240 / 1 / 50	V / Ph / Hz
<b>Energy Class</b>	Cooling / Heating	A++ / A+	-
<b>Pdesign</b>	Cooling / Heating	10,0 / 9,0	kW
<b>EER / COP</b>	-	3,33 / 3,53	W / W
<b>SEER / SCOP</b>	-	6,1 / 4,0	W / W
<b>Annual Electricity Consumption</b>	Cooling / Heating	533 / 3168	kWh
<b>Air Flow</b>	Indoor Unit	1500 / 1470 / 1380 / 1220	m <sup>3</sup> / h
<b>Sound Pressure Level at 1,4 m</b>	-	50 / 48 / 46 / 42	dB(A)
<b>Sound Power Level</b>	Indoor unit	59	dB(A)
<b>Refrigerant / Charge / Eq. CO2</b>	-	R32 / - / -	type / kg / t
<b>Refrigerant Liquid Pipe</b>	Diameter	3/8 / 9,5	inch / mm
<b>Refrigerant Gas Pipe</b>	Diameter	5/8 / 15,9	inch / mm
<b>Dimension (w x h x d)</b>	Indoor Unit	840 x 840 x 240	mm
<b>Dimension (w x h x d)</b>	Panel	950 x 950 x 52	mm
<b>Package (w x h x d)</b>	Indoor Unit	963 x 963 x 325	mm
<b>Package (w x h x d)</b>	Panel	1033 x 1038 x 112	mm
<b>Package volume</b>	Indoor unit	0,301	m <sup>3</sup>
<b>Package volume</b>	Panel	0,120	m <sup>3</sup>
<b>Net / Gross Weight</b>	Indoor Unit	31,0 / 38,0	kg
<b>Net / Gross Weight</b>	Panel	6,0 / 9,5	kg
<b>Set Temperature range</b>	-	16 ~ 30	°C

## Notes

The specification of products is subject to change based on further development of the units by the producer and can be changed without prior notice. Refer to rating label.

R32 (single component refrigerant HFC), GWP of refrigerant used: 675.

Contains fluorinated greenhouse gases covered by the Kyoto Protocol.