

# Sisäyksikkö Sinclair ASF-36BI seinäasenteinen

|                                       |                   |                   |                    |
|---------------------------------------|-------------------|-------------------|--------------------|
| <b>Power Supply</b>                   | Into Indoor Unit  | 220–240 / 1 / 50  | V / Ph / Hz        |
| <b>Energy Class</b>                   | Cooling / Heating | A++ / A+          | -                  |
| <b>Pdesign</b>                        | Cooling / Heating | 10,0 / 9,0        | kW                 |
| <b>EER / COP</b>                      | -                 | 3,03 / 3,43       | W / W              |
| <b>SEER / SCOP</b>                    | -                 | 6,1 / 4,0         | W / W              |
| <b>Annual Electricity Consumption</b> | Cooling / Heating | 561 / 3146        | kWh                |
| <b>Air Flow</b>                       | Indoor Unit       | 1600              | m <sup>3</sup> / h |
| <b>Sound Pressure Level at 1,4 m</b>  | -                 | 49 / 47 / 45 / 43 | dB(A)              |
| <b>Sound Power Level</b>              | Indoor unit       | 61                | dB(A)              |
| <b>Refrigerant / Charge / Eq. CO2</b> | -                 | R32 / - / -       | type / kg / t      |
| <b>Refrigerant Liquid Pipe</b>        | Diameter          | 3/8 / 9,5         | inch / mm          |
| <b>Refrigerant Gas Pipe</b>           | Diameter          | 5/8 / 15,9        | inch / mm          |
| <b>Dimension (w x h x d)</b>          | Indoor Unit       | 1200 x 665 x 235  | mm                 |
| <b>Package (w x h x d)</b>            | Indoor Unit       | 1363 x 770 x 300  | mm                 |
| <b>Package volume</b>                 | Indoor unit       | 0,315             | m <sup>3</sup>     |
| <b>Net / Gross Weight</b>             | Indoor Unit       | 32,0 / 38,0       | kg                 |
| <b>Set Temperature range</b>          | -                 | 16 ~ 30           | °C                 |

## Notes

The specification of products is subject to change based on further development of the units by the producer and can be changed without prior notice. Refer to rating label.  
R32 (single component refrigerant HFC), GWP of refrigerant used: 675.  
Contains fluorinated greenhouse gases covered by the Kyoto Protocol.