

Sisäyksikkö Sinclair ASH-36BIH seinäasenteinen

Capacity	Cooling / Heating	10,0 (1,2–10,5) / 12,0 (2,5–12,4)	kW
Power Supply	Into Indoor Unit	220–240 / 1 / 50	V / Ph / Hz
Energy Class	Cooling / Heating	A++ / A+	-
Pdesign	Cooling / Heating	10,0 / 9,0	kW
SEER / SCOP	-	6,1 / 4,0	W / W
Annual Electricity Consumption	Cooling / Heating	573 / 3149	kWh
Air Flow	Indoor Unit	1600	m ³ / h
Sound Pressure Level at 1 m	Indoor Unit	52 / 46 / 43	dB(A)
Sound Power Level	Indoor unit	57	dB(A)
Refrigerant / Charge / Eq. CO2	-	R32 / - / -	type / kg / t
Refrigerant Liquid Pipe	Diameter	3/8 / 9,5	inch / mm
Refrigerant Gas Pipe	Diameter	5/8 / 15,9	inch / mm
Dimension (w x h x d)	Indoor Unit	1350 x 326 x 253	mm
Package (w x h x d)	Indoor Unit	1441 x 421 x 367	mm
Net / Gross Weight	Indoor Unit	18,0 / 23,0	kg
Set Temperature range	-	16 ~ 30	°C

Notes

The specification of products is subject to change based on further development of the units by the producer and can be changed without prior notice. Refer to rating label.
R32 (single component refrigerant HFC), GWP of refrigerant used: 675.
Contains fluorinated greenhouse gases covered by the Kyoto Protocol.