

Ulkoyksikkö Sinclair SDV5-200EAS

Horse Power	HP	7	-
Power Supply	-	380–415 / 3 / 50	V / Ph / Hz
Capacity	Cooling	20,0	kW
Power Input	Cooling	5,28	kW
EER	-	3,79	kW / kW
Capacity	Heating	20,0	kW
Power Input	Heating	4,43	kW
COP	-	4,51	kW / kW
Combination of Indoor Units	-	50–130 % of Outdoor Unit Capacity	-
Number of indoor units	-	11	pcs
Compressor	Type	DC Inverter	-
Compressor	Quantity	1	-
Compressor	Oil	RB74AF	-
Operating Range - Cooling	-	- 5 ~ 48	°C
Operating Range - Heating	-	- 20 ~ 24	°C
Sound Pressure Level at 1 m	-	58	dB(A)
Sound power level	-	78	dB(A)
Airflow	-	9000	m ³ / h
Net Weight	-	143,0	kg
Gross Weight	-	159,0	kg
Net Dimension	w x h x d	1120 x 1558 x 528	mm
Packing Dimensions	w x h x d	1270 x 1575 x 565	mm
Refrigerant / Charge / Eq. CO2	-	R410A / 6,50 / 13,6	type / kg / t
Vertical Pipe Length	On Top / Bellow	Max. 50 / Max. 40	m
Pipe Length from 1. Branch	-	40	m
Equivalent Pipe Length	-	110	m
Total Pipe Length	-	150	m
Pipe Diameter	Liquid Side	9,5	mm
Pipe Diameter	Gas Side	19,1	mm