

MODEL				MV-E42BI + MV-H09BIF 4x, MV-H07BIF 1x					
FUNCTION				FUNCTION					
Cooling	Yes		Average season	Yes					
Heating	Yes		Warmer season	No					
			Colder season	No					
Design load			Seasonal efficiency						
Item	symbol	value	unit	Item	symbol	value	unit		
Cooling	Pdesignc	12,0	kW	Cooling	SEER	6,1	--		
Heating / Average	Pdesignh	11,8	kW	Heating / Average	SCOP/A	4,0	--		
Heating / Warmer	Pdesignh	-	kW	Heating / Warmer	SCOP/W	-	--		
Heating / Colder	Pdesignh	-	kW	Heating / Colder	SCOP/C	-	--		
Declared capacity for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj				Declared energy efficiency ratio, at indoor temperature 27(19)°C and outdoor temperature Tj					
Item	symbol	value	unit	Item	symbol	value	unit		
Tj = 35 °C	Pdc	12,10	kW	Tj = 35 °C	EERd	3,42	--		
Tj = 30 °C	Pdc	8,98	kW	Tj = 30 °C	EERd	4,87	--		
Tj = 25 °C	Pdc	5,75	kW	Tj = 25 °C	EERd	7,59	--		
Tj = 20 °C	Pdc	3,40	kW	Tj = 20 °C	EERd	9,66	--		
Declared capacity for heating/Average season, at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance / Average season, at indoor temperature 20 °C and outdoor temperature Tj					
Item	symbol	value	unit	Item	symbol	value	unit		
Tj = - 7 °C	Pdh	9,92	kW	Tj = - 7 °C	COPd	2,85	--		
Tj = 2 °C	Pdh	6,44	kW	Tj = 2 °C	COPd	4,06	--		
Tj = 7 °C	Pdh	4,18	kW	Tj = 7 °C	COPd	4,86	--		
Tj = 12 °C	Pdh	2,58	kW	Tj = 12 °C	COPd	5,30	--		
Tj = bivalent temperature	Pdh	8,70	kW	Tj = bivalent temperature	COPd	2,75	--		
Tj = operating limit	Pdh	9,99	kW	Tj = operating limit	COPd	2,99	--		
Declared capacity for heating / Warmer season, at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance / Warmer season, at indoor temperature 20 °C and outdoor temperature Tj					
Item	symbol	value	unit	Item	symbol	value	unit		
Tj = 2 °C	Pdh	-	kW	Tj = 2 °C	COPd	-	--		
Tj = 7 °C	Pdh	-	kW	Tj = 7 °C	COPd	-	--		
Tj = 12 °C	Pdh	-	kW	Tj = 12 °C	COPd	-	--		
Tj = bivalent temperature	Pdh	-	kW	Tj = bivalent temperature	COPd	-	--		
Tj = operating limit	Pdh	-	kW	Tj = operating limit	COPd	-	--		
Declared capacity for heating / Colder season, at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance / Colder season, at indoor temperature 20 °C and outdoor temperature Tj					
Item	symbol	value	unit	Item	symbol	value	unit		
Tj = - 7 °C	Pdh	-	kW	Tj = - 7 °C	COPd	-	--		
Tj = 2 °C	Pdh	-	kW	Tj = 2 °C	COPd	-	--		
Tj = 7 °C	Pdh	-	kW	Tj = 7 °C	COPd	-	--		
Tj = 12 °C	Pdh	-	kW	Tj = 12 °C	COPd	-	--		
Tj = bivalent temperature	Pdh	-	kW	Tj = bivalent temperature	COPd	-	--		
Tj = - 15 °C	Pdh	-	kW	Tj = - 15 °C	COPd	-	--		
Bivalent temperature				Operating limit temperature					
Item	symbol	value	unit	Item	symbol	value	unit		
Heating / Average	Tbiv	-6	°C	Heating / Average	Tol	-10	°C		
Heating / Warmer	Tbiv	-	°C	Heating / Warmer	Tol	-	°C		
Heating / Colder	Tbiv	-	°C	Heating / Colder	Tol	-	°C		
Cycling interval capacity				Cycling interval efficiency					
Item	symbol	value	unit	Item	symbol	value	unit		
For cooling	Pcycc	x,x	kW	For cooling	EERcyc	x,x	--		
For heating	Pcych	x,x	kW	For heating	COPcyc	x,x	--		
Degradation co-efficient cooling	Cdc	x,x	--	Degradation co-efficient heating	Cdh	x,x	--		
Electric power input in power modes other than 'active mode'				Annual electricity consumption					
Off mode	P _{OFF}	0,01239	kW	Cooling	Q _{CE}	689	kWh/a		
Standby mode	P _{SB}	0,01239	kW	Heating / Average	Q _{HE}	4130	kWh/a		
Thermostat-off mode	P _{TO}	0,01052/0,02627	kW	Heating / Warmer	Q _{HE}	-	kWh/a		
Crankcase heater mode	P _{CK}	0,000	kW	Heating / Colder	Q _{HE}	-	kWh/a		
Capacity control				Other items	symbol	value	unit		
Fixed	No		Sound power level (indoor/outdoor)	L _{WA}	55/70	dB(A)			
Staged	No		Global warming potential	GWP	675	kgCO ₂ eq.			
Variable	Yes		Rated air flow (indoor/outdoor)	--	560/7200	m ³ / h			
Name and address of the manufacturer or of its authorised representative.				Manufacturer: SINCLAIR Corp. Ltd., 1-4 Argyll St., London, UK					
				Representative: SINCLAIR EUROPE spol. s r.o., Purkynova 45, 612 00 Brno, CZ					
Contact details for obtaining more information				info@sinclair-solutions.com / www.sinclair-solutions.com					

* R32 (100% HFC-32)

* Device contains fluorinated greenhouse gases covered by the Kyoto Protocol.